



... for a brighter future

ITAPS Relations Interface: iRel

*Timothy J. Tautges
Mathematics & Computer Science Division
Argonne National Laboratory*



U.S. Department
of Energy



A U.S. Department of Energy laboratory
managed by The University of Chicago


Work performed by ANL for the U.S. DOE in support of the Global Nuclear Energy Partnership (GNEP). Views that may be expressed herein are those of the authors and are not necessarily representatives of the DOE or GNEP positions.





IRel: Relations Interface

- Purpose: relate entities between **iface1** and **iface2**, without making those interfaces depend on each other; relates:


Entity-Entity:



Entity-Set:



Entity-Both:



- “both”-type relations are for when
 - **Entity1** is related to multiple **Entity2**'s, and
 - **Set2** exists for each group of **Entity2**'s related to **Entity1**, and
 - You need fast retrieval of **Entity1** from **Entity2**
- Both-both relations *not* supported
- Examples:
 - iGeom Entity (vertex/curve/surface/volume) related to iMesh EntitySet containing mesh resolving the entity
 - Others? (fields-tags, ???)
- Lasso: infers relations based on matching iGeom (Entity/type/GLOBAL_ID) to iMesh (Entity set/GEOM_DIMENSION/GLOBAL_ID)



iRel Data Model

- enum Iface_Type: necessary because ITAPS C-based interfaces prepend interface name on function name
 - iRel_IBASE_IFACE, iRel_IGEOM_IFACE, iRel_IMESH_IFACE, iRel_IFIELD_IFACE, iRel_IREL_IFACE
- ent_or_set designation: 0=entity, 1=set, 2=both
- iRel_RelationHandle: object which stores instance handles being related, ent_or_set designations
- iBase_Instance, iBase_EntityHandle, iBase_EntitySetHandle: used to refer to instance/entity/set handles from arbitrary interfaces



iRel API

- `_newRel`, `_dtor`: create/destroy iRel instance
 - `_createRelation`, `destroyRelation`: create/destroy new relation
 - `_getRelatedInterfaces`: get interfaces related by a given relation handle
 - `_get/_set EntEnt/EntSet/SetEnt/SetSet Relation`: get/set relations between individual entities/sets
 - `_set EntEnt/SetEnt/EntSet/SetSet ArrRelation`: set relations between one and several entities/sets
 - `switch_order` parameter for designating iface single entity belongs to
 - `_get/_set EntArrEntArr/EntArrSetArr/SetArrEntArr/SetArrSetArr Relation`: get/set relations between pairs of entities/sets
 - `_create Vtx/Ent/VtxArr/EntArr AndRelate`: mesh creation functions which take related geometry entity
 - `_infer All/Ent/Set/EntArr/SetArr Relations`: infer relations (using criteria described earlier)
 - `_moveTo`: move entities related to specified geometry entity to that geometry entity
-
- All functions have “iRel” prepended to name, e.g. `iRel_newRel`
 - Include proposed API change from `Associat(e/ion)` to `Relat(e/ion)`



iRel Implementation

- Lasso (ANL) currently the only implementation
- iRel does *not* guarantee relations are persistent; that is, infer functions must be called every time
- This API and data model will probably change after iField is implemented, to handle relating fields (as entities, or other objects?) to tags

